

Comments on Barrier Buckets

Experience from the Fermilab Recycler


John Marriner

30 October 2002




f

What is the rf system?





f

Basically, it does work...



f


Sensitivity to Waveform



f

Sensitivity to waveform


- Require a uniform transfer function at harmonics of the revolution frequency (100 KHz) up to about 10 MHz
- Want voltage between barriers (nominally 0) to be less than 1% of peak
 - Want Gain flat to 1/4 dB
 - Phase flat to 2 degrees



f

The fundamental difference

- Particles captured by sine wave rf have oscillation frequencies near a non-zero value known as the synchrotron frequency.
- Particles capture by a barrier bucket have oscillation frequencies in a spread around zero.



f

The other fundamental difference

- Sine wave rf has only two variables: amplitude and phase. Mathematics is vector addition or multiplication of complex numbers.
- Barrier rf has quasi-infinite number of variables. Mathematics is Laplace transform.

f

Consequences for the Recycler

- Synchrotron motion is coupled to the Main Injector ramp
 - The accelerators share the same tunnel and stray magnetic fields from the Main Injector (<1 G) modulate the orbit length.
 - The modulation frequency is in the band of synchrotron frequencies.
- The resulting emittance growth in the Recycler is much bigger than what is acceptable (3x worse).
- Storage machines are more susceptible to this effect.

f

RF Feedback

- Conventional rf systems are rarely (if ever) true sine waves.
- A typical rf system is a modulated sinewave, where the bandwidth is typically larger than the synchrotron frequency spread to include features such as:
 - Radial position and phase feedback
 - Quadrupole
 - Tuning circuits
 - Beam loading compensation



f

Feedback with barriers

- Beam oscillations are very noticeable on the bunch profile displayed on an oscilloscope.
- We have identified two possible approaches
 - Narrow-band phase feedback system
 - Broad-band phase feedback system

f

Feedback System Concepts



f

Conclusions

- Attention to the precise waveform is important for the FNAL Recycler.
- Barrier bucket beams are susceptible to low frequency noise.
- Feedback systems may be required.
 - The requirements have not be fully explored.
 - The wide system bandwidth is both a problem an an opportunity.
 - Stability and effectiveness of these systems need study.
- We are early in the learning process.